



# Thumb Brake Master Cylinder

Lever ratio : 17mm / Piston diameter :  $\phi 12$

## ◆ Adjustable short lever



Item No.
GSTH12-17BAS

## ◆ Standard lever



Item No.
GSTH12-17B

## ◆ Option

※Master body mounting pitch 35mm



① Handle clamp  $\phi 22.2$



② Fork clamp  $\phi 50$

No.	Item No.
①	29000188
②	29000245

## How to Select a Thumb Brake Master Cylinder

① For mounting with handle clamps  
Adjustable short lever is recommended!



▲ Example of adjustable short lever installation

② For mounting with Fork clamps  
Standard levers are recommended! (Short is usable)



▲ Example of standard lever installation

# For Thumb Brake Rear Master Cylinder

Piston diameter  $\phi 12$



M10 x 1.0 threading on the reservoir tank mounting  
The banjo bolt can be connected directly to the reservoir tank.

Even if it is not for thumb brakes  
If you use the "Hose Adapter"  
Thumb brakes can be installed  
by using a hose adapter!



Mounting Pitch (Attaching bracket)	Color	Item No.	
		Rod / Rod End M6	Rod / Rod End M8
40mm/49mm	Black	RMC12-TH640B	RMC12-TH840B
	Brown	RMC12-TH640BR	RMC12-TH840BR
45mm	Black	RMC12-TH645B	RMC12-TH845B
	Brown	RMC12-TH645BR	RMC12-TH845BR
49mm (4mm offset)	Black	RMC12-TH649B	RMC12-TH849B
	Brown	RMC12-TH649BR	RMC12-TH849BR

## How to connect

